Applicant: Kimihiro Mabuchi et al. Attorney's Docket No.: 19461-0004US1 / 547267

Serial No.: 10/582,052 Filed: November 22, 2006 Page: 2 of 6

## Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

## Listing of Claims:

 (Currently Amended) A bundle of a plurality of selectively permeable polysulfone-based hollow fiber membranes, comprising a polysulfone-based resin and a hydrophilic polymer,

wherein each hollow fiber membrane has an inner surface for contacting blood and an outer surface for contacting a dialyzing fluid, the amount of a the hydrophilic polymer eluting from each hollow fiber membrane is not larger than 10 ppm, and the content of the hydrophilic polymer in the outer surface of a hollow fiber membrane is 25 to 50 mass %, characterized in that any of extracted solutions from ten fractions of said bundle, obtained by dividing said bundle at substantially regular intervals along the lengthwise direction, shows a maximum value of smaller than 0.10 in UV absorbance at a wavelength of 220 to 350 nm, with the proviso that said extracted solutions are obtained by the extraction method for tests regulated in the approval manufacturing standards for dialytic artificial kidney devices; and in that the difference between the maximum and the minimum out of the maximum values of UV absorbance of the extracted solutions from the respective fractions is not larger than 0.05.

- (Previously Presented) The bundle according to claim 1, wherein the bundle has substantially no partial sticking of the hollow fiber membranes in the lengthwise direction.
- (Previously Presented) The bundle according to claim 1, wherein the porosity of the outer surface of a hollow fiber membrane is 8 to 25%.
- (Previously Presented) The bundle according to claim 1, wherein the mass ratio of the hydrophilic polymer to the polysulfone-based resin is 1 to 20 mass %.

Applicant: Kimihiro Mabuchi et al. Attorney's Docket No.: 19461-0004US1 / 547267

Serial No.: 10/582,052 Filed: November 22, 2006

Page : 3 of 6

5. (Previously Presented) The bundle according to claim 1, wherein the hydrophilic

polymer is poly(vinylpyrrolidone).

6. (Previously Presented) The bundle according to claim 1, wherein the hydrophilic

polymer is crosslinked so as to be insoluble in water.

(Previously Presented) The bundle according to claim 1, which is used in a blood

purifier.

8. (Withdrawn) A process for manufacturing a bundle of selectively permeable

polysulfone-based hollow fiber membranes, characterized in that the direction of feeding an air

to dry the bundle of hollow fiber membranes is inverted alternately at given time intervals.

9. (Withdrawn) The process according to claim 8, wherein, in drying the bundle of

hollow fiber membranes by feeding an air to said bundle, the capacity of the air to be fed and the drying temperature are decreased in accordance with a decrease in the moisture content of said

bundle.

10. (Withdrawn) A process for manufacturing a bundle of selectively permeable

polysulfone-based hollow fiber membranes, characterized in that the bundle of hollow fiber

membranes is dried by irradiation with microwaves under a reduced pressure.

11. (Withdrawn) The process according to claim 10, wherein the bundle of hollow

fiber membranes is dried under a reduced pressure of 0.1 to 20 kPa.

12. (Withdrawn) The process according to claim 10, wherein the bundle of hollow

fiber membranes is dried by irradiation with microwaves having a low output of not higher than

20 kW.

Applicant: Kimihiro Mabuchi et al. Attorney's Docket No.: 19461-0004US1 / 547267

Serial No.: 10/582,052 Filed: November 22, 2006

Page : 4 of 6

13. (Withdrawn) The process according to claim 10, wherein the bundle of hollow fiber membranes is dried while the output of microwaves is being decreased in accordance with a decrease in the moisture content of the bundle of hollow fiber membranes.

- 14. (Withdrawn) The process according to claim 10, wherein the bundle of hollow fiber membranes is dried while the output of microwaves is being sequentially decreased in three steps in accordance with a decrease in the moisture content of the bundle of hollow fiber membranes.
- (Withdrawn) The process according to claim 10, wherein the bundle of hollow fiber membranes is dried at a temperature of 30 to 90°C.
- 16. (Withdrawn) A process for manufacturing a bundle of selectively permeable polysulfone-based hollow fiber membranes, characterized in that the bundle of hollow fiber membranes is dried by combined drying steps, comprising a step of drying the bundle by irradiation with microwaves under a reduced pressure, and a step of drying the bundle by feeding an air to said bundle while inverting the air-feeding direction alternately at given time intervals.
- 17. (New) The bundle of claim 1, wherein the content of the hydrophilic polymer in the outer surface of the hollow fiber membrane is determined by the weight of the hydrophilic polymer in the outer surface divided by the total weight of the hydrophilic polymer and the polysulfone-based resin in the outer surface.